Observation of the optical analogue of the quantised conductance of a point contact

E.A. Montie, E.C. Cosman, G.W. 't Hooft, M.B. van der Mark and C.W.J. Beenakker
Philips Research Laboratories, P.O. Box 80000, 5600 JA Eindhoven, The Netherlands

The light power transmitted by a diffusively illuminated slit of finite thickness is observed to depend stepwise on the slit width. The steps have equal height and a width of one half the wavelength of the monochromatic light used. This novel diffraction phenomenon is the analogue of the quantization of the conductance of a point contact in a two-dimensional electron gas. In contrast to the electronic case, absorption at the walls of the slit plays an important role in determining the shape of the steps, as we show from a model calculation.

1. Introduction

Diffraction of light by an aperture is an easily observed and widely known manifestation of the wave nature of light. As a direct consequence of this diffraction, the transmission cross-section σ of an aperture for an incident plane wave differs from its geometrical area A . The relation between σ and A is a function sensitive to the detailed properties of the aperture [1–4].

Recently, it was pointed out that this relation is remarkably simplified for the case of diffuse (i.e. isotropic rather than plane-wave) illumination [5]. It was predicted that σ increases with A in a series of steps of equal height. A similar simplification occurs for two-dimensionally diffuse illumination of a slit, in a plane perpendicular to the slit. The transmission cross-section per unit length of the slit, σ' , is predicted to increase stepwise as a function of its width W . The steps occur whenever $W = n\lambda/2$, with $n = 1, 2, 3, \dots$, i.e. when a new mode is enabled in the slit. The diffuse illumination is required to couple equally to all modes [5].

The optical transmission characteristics of a slit have been studied extensively for *plane wave* illumination [6–9]. It was but recently, that the first observations of the discretised transmission cross-section for diffuse illumination were reported [10], analogously to the discretised con-

ductance of a quantum point contact [11, 12]. In this paper we summarise our findings and discuss some (not previously published) calculations on the influence of absorption on the shape of the transmission steps.

2. The experiment

We did the experiment at a wavelength of $1.55 \mu\text{m}$. The set-up is presented schematically in fig. 1. The device consists of two halves of an integrating sphere (40 mm diameter) made of aluminum and coated with diffusively scattering barium sulfate. The slit is at the top of the sphere where the metal is only $25 \mu\text{m}$ thick. Inside the slit, the aluminum is covered with silver to obtain a high reflection coefficient, which is required to avoid destruction of the transmission staircase by excessive absorption at the walls of the slit. The transmitted light was collected by the integrating sphere and detected. The slit width was varied by a piezo-electric transducer, and was monitored by a Michelson interferometer.

The laser beam was expanded by a microscope objective and scattered by a diffusor. Diffuse illumination in *two dimensions* only (no propagation in the direction parallel to the slit) is crucial to the experiment since a slit rather than an

Fig 1 Schematic illustration of the set-up

aperture was used. Due to the large bandwidth of the laser (15 nm), the illumination was essentially incoherent.

The experimental results are presented in fig. 2, which shows the transmitted power as a function of the slit width. Trace (a) was obtained

Fig 2. Transmitted power as a function of the slit width W , using a paper diffuser (a) and a glass-fibre diffuser (b), trace b is scaled and shifted vertically for clarity. The inset shows an enlarged part of trace b

using a paper diffuser and two slits in order to make the light diffusive in a *plane* only. Trace (b) was obtained using a diffuser made of very many parallel glass fibres [13]. Because the latter method is intrinsically two-dimensional, it produces a higher illumination intensity, and thus a better signal-to-noise ratio. A stepwise increase of the transmitted power is clearly observed in both traces. The steps occur at $\lambda/2$ intervals in W , as predicted [5]. We also see that all steps have an *equal height*, implying that each mode transmits the same power. Because for large slit widths ($W/\lambda \rightarrow \infty$) σ' is equal to W , the steps in σ' must be equal to $\lambda/2$, the size of the intervals in W .

3. The shape of the steps

The steps in the transmission cross-section are not abrupt. Partly, this is caused by non-uniformities in the slit width. Another cause is the slight absorption of radiation at the walls of the slit, which remains in spite of the use of a silver coating. The resulting damping of the propagating modes [13] causes a rounding of the steps and a slight curvature of the staircase for the first few steps visible in trace (a). Rounding of the steps is also partly due to non-adiabatic coupling (with inter-mode scattering) between the narrow slit and the infinite space [14].

The polarisation (the direction of the electric field) of the (two-dimensionally) diffusive light can be chosen to be either parallel (TE mode) or perpendicular (TM mode) to the direction of the slit. The attenuation of light in the slit for the TE and TM polarisation differs significantly. This absorption results from the penetration of the electric field in the (finitely conductive) metal. For a TM mode, the field perpendicular to the slit is constant, but for a TE mode the field is (in the ideal case) a sine (see fig. 3), and thus has much more field energy in the slit than in the conductors. Hence the attenuation of the TM modes will be much larger than for the TE modes.

The effect of absorption on the shape of the steps does not play a role in the electronic

Fig 3 The mode profiles of the two lowest TE₁ and TE₂ modes in a perfectly conducting parallel plate waveguide of width W . The solid arrows represent the electric field E and the propagation of the wave is in the z direction.

counterpart, and has therefore not been investigated previously. To study this effect we will now calculate the attenuation of the TE modes in a lossless dielectric between two infinitely large conducting plates at a distance W , starting from Maxwell's equations [15]. The wave equation is

$$\nabla^2 E(x, y, z) = -\mu\epsilon\omega^2 E(x, y, z), \quad (1)$$

which also holds for the magnetic field H , and where the time dependence $\exp(i\omega t)$ has already been accounted for by insertion of $i\omega$ for the operator $\partial/\partial t$. We identify $\mu\epsilon\omega^2 = k^2 = k_x^2 + k_y^2 + k_z^2$, with k complex. With ϵ_d and $\epsilon_c = \epsilon'_c + i\epsilon''_c$ the permittivity of the dielectric and conductor, respectively, we have $\mu_0\epsilon_0\epsilon_d\omega^2 \equiv k_d^2$ and $\mu_0\epsilon_0(\epsilon'_c + i\epsilon''_c)\omega^2 \equiv k_c^2$.

The propagation constants in the conductor and the dielectric should be matched, so $k_z \equiv k_{z,c} = k_{z,d}$, and because we use a plane wave propagating in the z -direction, $k_{x,c} = k_{x,d} = 0$. We find that $k_{y,c}^2 - k_c^2 = -k_z^2 = -k_{y,d}^2 - k_d^2$.

After putting the proper boundary conditions on the interface of the conductors and dielectric at $y = \pm W/2$ we eventually find

$$\frac{\pm k_{y,d}^2 \exp(-ik_{y,d}W)}{[1 \pm \exp(-ik_{y,d}W)]^2} = \mu_0\epsilon_0\omega^2(\epsilon'_c - \epsilon_d + i\epsilon''_c), \quad (2)$$

where the $\pm$ sign selects between the even and odd TE _{n} modes. In a cavity without loss we find $k_{y,d}W = n\pi$. If we now use that $k_{x,d}^2 + k_{y,d}^2 + k_{z,d}^2 \equiv k_d^2$, with $k_{x,d} = 0$, $k_{z,d} \equiv k_z \equiv k'_z + ik''_z$, and $k_d^2 = \epsilon_d k_{v,ic}^2$, we find the complex wave vector in

Fig 4 Calculated rounding of the steps due to absorption for a silver screen of thickness $L = 25 \mu\text{m}$ at a wavelength of $\lambda = 1.55 \mu\text{m}$.

the propagation direction

$$k'_z + ik''_z = \sqrt{\epsilon_d k_{v,ic}^2 - k_{y,d}^2} \quad (3)$$

The absorption for the intensity of the n th mode corresponding to this wave vector in a guide of length L is then given by

$$T_n = \exp(-2k''_z L) \quad (4)$$

In fig 4 the calculated total transmission $T = \sum_n T_n$ is shown versus the width W for the TE _{n} modes of a parallel-plane waveguide. We used the dielectric constant of silver [16] at a wavelength $\lambda_{v,ic} = 1.55 \mu\text{m}$. It implicitly is assumed that the thickness of the plates $L = 25 \mu\text{m}$ is much larger than their mutual distance W , and that all modes were equally excited.

The rounding of the steps visible in fig 4 is due entirely to absorption, since the rounding due to the intermode scattering at entrance and exit of the slit [14] has been neglected in this calculation.

4. Discussion

In conclusion, we have reported the observation of the optical analogue of the conductance quantization of a point contact. We calculated

the rounding of the steps resulting from absorption in the case of TE polarisation

It is remarkable that this optical phenomenon, with its distinctly 19th century flavour, was not noticed prior to the discovery of its electronic counterpart. There is an interesting parallel in the history of the discovery of the two phenomena. In the electronic case, the Landauer formula

$$G = \frac{e^2}{h} \sum_{n=1}^N T_n, \quad (5)$$

was already known *before* the quantised conductance of a point contact was discovered. The reason that this discovery came as a surprise, was that the relation $G = (e^2/h)N$ (following from the Landauer formula for $T_n = 1$) was regarded as an order of magnitude estimate [17]. In order to have true quantisation, the relative error in this estimate must be smaller than $1/N$, which at that time was not obvious.

The equivalent of the Landauer formula in optics for the transport of electromagnetic modes has been known for a long time. It is interesting to see that also in this field it was not noticed that the relation $T = N$ holds with a better than $1/N$ accuracy. This is particularly apparent in, for example, a paper by Snyder and Pask [18], where they expect the relation $T \approx N$ to hold only in the geometrical optics limit, $\lambda \rightarrow 0$.

Acknowledgements

We thank Professor J P Woerdman for drawing our attention to the optical equivalent of the Landauer formula. We are grateful to G J J Geboers and A W Sleutjes for the fabrication of the slit. Discussions with Q H F Vreken and H van Houten were very valuable. We would like to thank P J A Thijs for providing a high-power semiconductor laser.

References

- [1] C I Bouwkamp Rep Progr Phys 17 (1954) 35
- [2] R W P King and T T Wu in The Scattering and Diffraction of Waves (Harvard University Press Cambridge 1959) p 113
- [3] J J Bowman, T B A Senior and P L E Uslenghi Electromagnetic and Acoustic Scattering by Simple Shapes (North Holland Amsterdam 1969)
- [4] J D Jackson Classical Electrodynamics 2nd Ed (Wiley New York 1975)
- [5] H van Houten and C W J Beenakker in Analogies in Optics and Micro Electronics eds W van Haeringen and D Lenstra (Kluwer Dordrecht 1990) p 203
- [6] S C Kashyap and M A K Hamid IEEE Trans on Antennas and Propagation 19 (1971) 499
- [7] F L Neerhoff and G Mur Appl Sci Res 28 (1973) 73
- [8] A Z Elsherbeni and M Hamid Can J Phys 65 (1987) 16
- [9] M T Lightbody and M A Fiddy Adv Electron Electron Phys 19 (1987) 61
- [10] E A Montie, E C Cosman, G W t Hooft, M B van der Mark and C W J Beenakker Nature 350 (1991) 594
- [11] B J van Wees, H van Houten, C W J Beenakker, J G Williamson, L P Kouwenhoven, D van der Marel and C T Foxon Phys Rev Lett 60 (1988) 848
- [12] D A Wharam, T J Thornton, R Newbury, M Pepper, H Ahmed, J E F Frost, D G Hasko, D C Peacock, D A Ritchie and G A C Jones J Phys C 21 (1988) L209
- [13] M B van der Mark Thesis University of Amsterdam (1990)
- [14] A Szafer and A D Stone Phys Rev Lett 62 (1989) 300
- [15] H A Atwater Introduction to Microwave Theory (McGraw Hill 1962)
- [16] G Hass and L Hadley Optical Properties of Metals American Institute of Physics Handbook 2nd Ed (McGraw Hill 1963) p 6
- [17] Y Imry in Directions in Condensed Matter Physics eds G Grinstein and G Mazenko (World Scientific Singapore 1986) p 130
- [18] A W Snyder and C Pask J Opt Soc Am 63 (1973) 806