

#### Asynchronous Programming in the Abstract Behavioural Specification Language

Azadbakht, K.

#### Citation

Azadbakht, K. (2019, December 11). Asynchronous Programming in the Abstract Behavioural Specification Language. Retrieved from https://hdl.handle.net/1887/81818

Version:	Publisher's Version
License:	<u>Licence agreement concerning inclusion of doctoral thesis in the</u> <u>Institutional Repository of the University of Leiden</u>
Downloaded from:	https://hdl.handle.net/1887/81818

Note: To cite this publication please use the final published version (if applicable).

Cover Page



## Universiteit Leiden



The handle <u>http://hdl.handle.net/1887/81818</u> holds various files of this Leiden University dissertation.

Author: Azadbakht, K. Title: Asynchronous Programming in the Abstract Behavioural Specification Language Issue Date: 2019-12-11

### Part II

# Case Study: Preferential Attachment in ABS

This part consists of the following chapters:

**Chapter 2** The Barabasi-Albert model (BA) is designed to generate scale-free networks using the preferential attachment mechanism. In the preferential attachment (PA) model, new nodes are sequentially introduced to the network and they attach preferentially to existing nodes. PA is a classical model with a natural intuition, great explanatory power and interesting mathematical properties. Therefore, PA is widely-used for network generation. However the sequential mechanism used in the PA model makes it an inefficient algorithm. The existing parallel approaches, on the other hand, suffer from either changing the original model or explicit complex low-level synchronization mechanisms. In this chapter we investigate a high-level Actor-based model of the parallel algorithm of network generation and its scalable mult-core implementation in the ABS language.

**Chapter 3** Generation of social networks using Preferential Attachment (PA) mechanism introduced in previous chapter features interesting mathematical properties which only appear in large-scale networks. However generation of such extralarge networks can be challenging due to memory limitations. In this chapter, we investigate a distributed-memory approach for PA-based network generation which is scalable and which avoids low-level synchronization mechanisms thanks to utilizing the powerful programming model and proper programming constructs of the ABS language.