



Universiteit
Leiden
The Netherlands

On the power efficiency, low latency, and quality of service in network-on-chip

Wang, P.

Citation

Wang, P. (2020, February 12). *On the power efficiency, low latency, and quality of service in network-on-chip*. Retrieved from <https://hdl.handle.net/1887/85165>

Version: Publisher's Version

License: [Licence agreement concerning inclusion of doctoral thesis in the Institutional Repository of the University of Leiden](#)

Downloaded from: <https://hdl.handle.net/1887/85165>

Note: To cite this publication please use the final published version (if applicable).

Cover Page



Universiteit Leiden



The handle <http://hdl.handle.net/1887/85165> holds various files of this Leiden University dissertation.

Author: Wang, P.

Title: On the power efficiency, low latency, and quality of service in network-on-chip

Issue Date: 2020-02-12

On the Power Efficiency, Low Latency, and Quality of Service in Network-on-Chip

Peng Wang

On the Power Efficiency, Low Latency, and Quality of Service in Network-on-Chip

PROEFSCHRIFT

ter verkrijging van
de graad van Doctor aan de Universiteit Leiden,
op gezag van Rector Magnificus Prof.mr. C.J.J.M. Stolker,
volgens besluit van het College voor Promoties
te verdedigen op woensdag 12 februari 2020
klokke 11:15 uur

door

Peng Wang
geboren te Liaoning, China
in 1990

Promotor:	Dr. Todor P. Stefanov	Universiteit Leiden
Second-Promotor:	Prof. Dr. Joost N.Kok	Universiteit Leiden
Promotion Committee:	Prof. Dr.-ing Diana Göhringer Prof. Dr. Georgi Gaydadjiev Prof. Dr. Kees G.W. Goossens Prof. Dr. Aske Plaat Prof. Dr. Harry A.G. Wijshoff Prof. Dr. Fons J. Verbeek	Technische Universität Dresden Rijksuniversiteit Groningen Technische Universiteit Eindhoven Universiteit Leiden Universiteit Leiden Universiteit Leiden

On the Power Efficiency, Low Latency, and Quality of Service in Network-on-Chip

Peng Wang. -

Dissertation Universiteit Leiden. - With ref. - With summary in Dutch.

Copyright © 2019 by Peng Wang. All rights reserved.

This dissertation was typeset using L^AT_EX in Linux.

Cover designed by Jian Zhang

ISBN: 978-90-9032677-1

Printed in the Netherlands.

Contents

Contents	v
List of Figures	ix
List of Tables	xi
List of Abbreviations	1
1 Introduction	1
1.1 Design Trends in Network-on-Chip	3
1.1.1 Low Power Consumption	3
1.1.2 Low Latency	4
1.1.3 Advanced Quality of Service	5
1.2 Contradictions between Design Trends	6
1.3 Problem Statement	7
1.3.1 Problem 1	7
1.3.2 Problem 2	8
1.4 Contributions of The Thesis	9
1.5 Thesis Outline	12
2 Background	13
2.1 Network-on-Chip	13
2.1.1 Network Topologies	14
2.1.2 Routing Approaches	16
2.1.3 Flow Control Approaches	18
2.1.4 Router Architecture in NoCs	20
2.2 Power Consumption Analysis	23
2.3 Conventional Power Gating in A NoC	24

3 Duty Buffer Based Power Gating Approach	27
3.1 Problem Statement	27
3.2 Contributions	28
3.3 Related work	29
3.4 DB-based Approach	30
3.4.1 Input Port with Duty Buffer	31
3.4.2 Power Gating on VCs	32
3.4.3 Power Gating Scheme	33
3.5 Experimental Results	36
3.5.1 Evaluation on Synthetic Workloads	37
3.5.2 Evaluation on Real Application Workloads	39
3.6 Discussion	41
4 D-bypass Power Gating Approach	43
4.1 Problem Statement	43
4.2 Contributions	45
4.3 Background	46
4.4 Related Work	47
4.5 D-bypass Approach	48
4.5.1 Extended Router Structure	48
4.5.2 An Example of the Reservation Process	50
4.5.3 Power Gating Conditions	52
4.6 Experimental Results	53
4.6.1 Evaluation on Synthetic Workloads	54
4.6.2 Evaluation on Real Application Workloads	57
4.7 Discussion	60
5 EVC-based Power Gating Approach	61
5.1 Problem Statement	61
5.2 Contributions	62
5.3 Background	63
5.4 Related Work	64
5.5 Our EVC-based Power Gating	66
5.5.1 Distribution of Virtual Bypass Paths	66
5.5.2 Extended Router Structure	67
5.5.3 Power Gating Scheme	68
5.5.4 Example of Our Power Gating Approach	69
5.5.5 Resolving Starvation	71
5.6 Experimental Results	71
5.6.1 Evaluation on Synthetic Workloads	73

5.6.2	Evaluation on Real Application Workloads	75
5.7	Discussion	77
6	Energy-Efficient Confined-interference Communication	79
6.1	Problem Statement	79
6.2	Contributions	81
6.3	Background	82
6.3.1	Surf-routing	82
6.3.2	BLESS-routing	83
6.4	Related Work	83
6.5	Surf-Bless Routing Approach	85
6.5.1	Wave Pattern in Surf-Bless	85
6.5.2	Router Architecture	87
6.5.3	Surf-Bless routing algorithm	88
6.6	Experimental Results	89
6.6.1	Evaluation on Synthetic Workloads	90
6.6.2	Transfer of Multiple Class Packets	94
6.7	Discussion	97
7	Summary and Conclusion	99
Bibliography		105
List of Publications		113
Samenvatting		117
Acknowledgements		119
Curriculum Vitae		121

List of Figures

1.1	Contributions outline.	9
2.1	An example of a many-core system.	14
2.2	Classical network topologies.	15
2.3	Deadlock caused by cyclic dependency of packets.	17
2.4	A timeline example of a credit-based flow control.	19
2.5	Router architecture.	20
2.6	Router pipeline.	22
2.7	Power consumption in a 8×8 2D mesh NoC.	23
2.8	Conventional NoC power gating.	24
2.9	Wakeup process.	25
3.1	The NoC structure and extended input port and output port.	31
3.2	Controllers for input and output ports.	34
3.3	The interactive process between an output port in the upstream router and the input port in the corresponding downstream router.	35
3.4	Average packet latency across full range of workloads.	37
3.5	The average packet latency.	39
3.6	The breakdown of the NoC power consumption.	40
4.1	Node-Router Decoupling.	46
4.2	Extended router structure in D-bypass.	49
4.3	Example of the reservation process.	50
4.4	Packet latency across different injection rates.	55
4.5	Power consumption across different injection rates.	56
4.6	Execution time.	57
4.7	Average packet latency.	58
4.8	Breakdown of the NoC power consumption.	59
5.1	Express virtual channel.	64

5.2	Extended EVC-based power gating approach.	67
5.3	An example of our power gating approach.	70
5.4	Latency across different injection rates.	73
5.5	Power consumption across different injection rates.	74
5.6	Execution time.	75
5.7	Average network latency.	76
5.8	Power consumption.	77
6.1	Confined-interference communication on a NoC.	80
6.2	The wave pattern in Surf-routing.	83
6.3	Wave pattern in Surf-Bless routing.	86
6.4	Router architecture in Surf-Bless.	87
6.5	Non-interference between domains.	91
6.6	Energy consumption across different number of domains.	92
6.7	Latency across different number of domains.	93
6.8	Application execution time.	94
6.9	NoC packet latency.	95
6.10	NoC energy consumption.	96
7.1	Packet latency (PL) and power consumption (PC) at low traffic workloads (l), medium traffic workloads (m), and high traffic workloads (h).	100

List of Tables

1.1	NoCs on real chips.	3
3.1	Parameters.	36
3.2	Area of router components.	41
4.1	Parameters.	54
5.1	Parameters used in experiments.	72
6.1	Parameters.	90

