



Universiteit
Leiden
The Netherlands

Towards superconducting spintronics with RuO₂ and CrO₂ nanowires

Prateek, K.

Citation

Prateek, K. (2023, December 8). *Towards superconducting spintronics with RuO₂ and CrO₂ nanowires*. *Casimir PhD Series*. Retrieved from <https://hdl.handle.net/1887/3666050>

Version: Publisher's Version

License: [Licence agreement concerning inclusion of doctoral thesis in the Institutional Repository of the University of Leiden](#)

Downloaded from: <https://hdl.handle.net/1887/3666050>

Note: To cite this publication please use the final published version (if applicable).

Propositions

accompanying the thesis

Towards Superconducting Spintronics with RuO₂ and CrO₂ Nanowires

1. The morphology and transport properties of selective area grown CrO₂ 'easy' wires (wires directed along the magnetic easy axis) are very different from 'hard' wires, unlike the easy and hard axis wires obtained from Ar-etched CrO₂ films. (*Chapter 3 of this thesis*)
2. The critical current density for the depinning of a magnetic domain wall in CrO₂ wires is of the same order as in conventional ferromagnets like Permalloy. The nearly 100% spin polarization in CrO₂ does not lead to reduction in depinning critical current density. (*Chapter 4 of this thesis*)
3. The temperature dependence of the critical current in weak links of antiferromagnetic RuO₂ is different from that in normal metal weak links, where it is governed by diffusive dephasing of Cooper pairs under the influence of temperature. Instead, a temperature-independent mechanism appears to take over at low temperatures around 2K. (*Chapter 5 of this thesis*)
4. Depositing a thin layer of protective material like RuO₂ *in situ* with CrO₂ is probably a more controlled process than Ar-etching the insulating oxide layer in a low pressure oxygen deficient system. (*Chapter 6 of this thesis*)
5. Pendio-epitaxial non uniform growth of CrO₂ wires inside the trenches probably is indicative of residues of SiO₂ at the surface of the trench. (*A. Singh et al., Phys. Rev. X 6, 041012 (2016)*)
6. The spin polarization nature of supercurrents in ferromagnets remains to be observed or demonstrated, for instance by observing the interaction of the supercurrent with a magnetization or a domain wall. (*J. Linder et al., Nat. Phys. 11, 307–315 (2015)*)
7. Even though the ferromagnetic Heusler alloy Co₂FeAl_{0.5}Si_{0.5} only has 80% spin polarization, this is still significantly larger than the spin polarization found in ³d ferromagnets. The material might be a good candidate to study long range proximity effects, because it should be easier to fabricate transparent interfaces. (*M. Vahidi et al., APL Materials 2, 046108 (2014)*).
8. It has been shown that supercurrents can also be induced in van der Waals-type ferromagnets. These materials bring new possibilities, because the magnetism can be influenced by electrical gates. (*G. Hu et al., Nature Comm. 14, 1779 (2023)*)
9. An unsuccessful research is much riskier for a PhD candidate than for researchers with a permanent position.

Kumar Prateek
Leiden, 08th December 2023